



Polysystem Cleaner

Description

Polysystem Cleaner: Liquid for cleaning Polysystem Membranes and accessories. Use on aged membranes and membranes which have been exposed to dust or atmospheric pollution.

Usage

Apply Polysystem Cleaner to a cloth then rub the membrane surface.

Wait for Polysystem cleaner to evaporate completely before welding membranes. Dry time will not exceed a few minutes.

Polysystem Cleaner does not require dilution.

The usage of Polysystem Cleaner must be used for all remedial works where the membrane is aged or dirty.

Polysystem membranes stored in their original packaging will not require cleaning.

If membranes are exceptionally dirty a preliminary cleaning with soap and water is recommended before using Polysystem Cleaner.

Polysystem Cleaner should be used on all accessories, such as sheet laminated metal, before welding commences, to remove any impurities from the surfaces.

Product benefits of Polysystem Membranes



EXCELLENT

ENVIRONMENTALLY FRIENDLY SOLUTION

Polysystem membranes are 100% recyclable, including packaging such as tapes and labels.



SUPERIOR

SPEED AND SAFETY DURING INSTALLATION



EXCELLENT

RESISTANCE TO HIGH AND LOW TEMPERATURE



SUPERIOR

LIFE SPAN



EXCELLENT

RESISTANCE TO UV RADIATION

Polysystem membranes do not require any kind of protection and can be directly exposed to the elements.



EXCELLENT

PUNCTURE RESISTANCE

Polysystem membranes perform excellently when mechanically fastened.

Characteristics

Value

Form

Transparent liquid

Packaging

5 litre can



POLISYSTEM UK LTD.®

